




UNITRONIC® LiYCY

Screened data transmission cable with colour code acc. to DIN 47100



Benefits

- Overall braid minimises electrical interference
- Multifunctional application possibilities

Application range

- Screened cables with small dimensions are suitable for use in computer systems, instrumentation technology, office equipment, balances.
- Dry or damp rooms

Product features

- Flame-retardant according IEC 60332-1-2

Norm references / Approvals

- Based on VDE 0812

Product make-up

- Fine-wire/multi-wire (0.34 mm²) strand made of bare copper wires
- Core insulation made of PVC
- Tinned-copper braiding
- Outer sheath made of PVC
Outer sheath colour: pebble grey (RAL 7032)

Technical data

- Core identification code**
DIN 47100 without colour repetition, refer to Appendix T9
- Mutual capacitance**
C/C: approx. 120 nF/km
C/S: approx. 160 nF/km
- Peak operating voltage**
(not for power applications)
at 0.14 mm²: 350 V
at ≥ 0.25 mm²: 500 V
- Specific insulation resistance**
> 20 GOhm x cm
- Inductivity**
approx. 0.65 mH/km
- Conductor stranding**
Stranded, fine-wire
0.34 mm²: 7-wire
- Minimum bending radius**
Occasional flexing: 15 x outer diameter
Fixed installation: 6 x outer diameter
- Test voltage**
At 0.14 mm²: 1200 V
≥ 0.25 mm²: 1500 V
- Temperature range**
Occasional flexing: -5°C to +70°C
Fixed installation: -40°C to +80°C

Article number	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
UNITRONIC® LiYCY				
0034302	2 x 0.14	3.9	12.0	20
0034303	3 x 0.14	4.1	13.0	28
0034304	4 x 0.14	4.3	14.3	33
0034305	5 x 0.14	4.6	15.5	38
0034306	6 x 0.14	4.9	18.2	38
0034307	7 x 0.14	4.9	19.0	49
0034308	8 x 0.14	5.8	21.2	56
0034310	10 x 0.14	6.1	28.5	66
0034312	12 x 0.14	6.3	30.4	78
0034314	14 x 0.14	6.7	32.0	80
0034315	15 x 0.14	6.9	37.8	86
0034316	16 x 0.14	7.0	43.0	90
0034318	18 x 0.14	7.3	48.8	104
0034320	20 x 0.14	7.7	53.9	116
0034321	21 x 0.14	7.9	55.5	121
0034324	24 x 0.14	8.4	61.0	132
0034325	25 x 0.14	8.5	63.0	149
0034328	28 x 0.14	8.5	66.1	153
0034330	30 x 0.14	8.7	69.0	158
0034332	32 x 0.14	9.0	73.6	164
0034336	36 x 0.14	9.3	83.0	183
0034340	40 x 0.14	10.4	87.5	210
0034344	44 x 0.14	10.7	110.5	225
0034350	50 x 0.14	11.1	122.5	253
0034402	2 x 0.25	4.5	16.0	32
0034403	3 x 0.25	4.7	21.0	37
0034404	4 x 0.25	5.0	24.0	41.3
0034405	5 x 0.25	5.6	29.0	51.2
0034406	6 x 0.25	6.0	30.0	58
0034407	7 x 0.25	6.0	37.0	65
0034408	8 x 0.25	7.1	42.0	73
0034410	10 x 0.25	7.5	46.0	82
0034412	12 x 0.25	7.7	53.0	98
0034414	14 x 0.25	8.0	59.0	99
0034415	15 x 0.25	8.3	61.0	111
0034416	16 x 0.25	8.4	64.0	124
0034418	18 x 0.25	8.8	83.0	143
0034420	20 x 0.25	9.3	88.0	152.3

Article number	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
0034421	21 x 0.25	9.6	93.0	161
0034425	25 x 0.25	10.7	114.0	172
0034428	28 x 0.25	10.8	126.0	181.1
0034430	30 x 0.25	11.0	132.0	189
0034432	32 x 0.25	11.4	138.0	203
0034436	36 x 0.25	11.8	148.0	220
0034440	40 x 0.25	12.7	157.0	248
0034450	50 x 0.25	13.8	178.0	318
0034461	61 x 0.25	15.0	205.0	365.2
0034502	2 x 0.34	4.9	21.0	37
0034503	3 x 0.34	5.1	27.0	49
0034504	4 x 0.34	5.7	28.0	59
0034505	5 x 0.34	6.2	30.0	66
0034506	6 x 0.34	6.8	45.0	79
0034507	7 x 0.34	6.8	48.0	83
0034508	8 x 0.34	7.8	52.0	94
0034510	10 x 0.34	8.3	74.0	129.2
0034512	12 x 0.34	8.5	80.0	142
0034514	14 x 0.34	8.9	86.0	154
0034515	15 x 0.34	9.2	90.0	155
0034516	16 x 0.34	9.4	94.0	160
0034518	18 x 0.34	10.2	103.0	173
0034520	20 x 0.34	10.7	112.0	192
0034521	21 x 0.34	11.1	116.0	199.2
0034525	25 x 0.34	11.9	135.0	259
0034528	28 x 0.34	12.0	153.0	280
0034530	30 x 0.34	12.3	159.0	291.1
0034532	32 x 0.34	13.0	165.0	305
0034536	36 x 0.34	13.4	179.0	331
0034540	40 x 0.34	14.8	200.0	365
0034550	50 x 0.34	15.9	235.0	431
0034602	2 x 0.50	5.6	29.0	54
0034603	3 x 0.50	5.9	38.0	67
0034604	4 x 0.50	6.3	43.0	77
0034605	5 x 0.50	7.0	51.0	90
0034606	6 x 0.50	7.6	59.0	104
0034607	7 x 0.50	7.6	65.0	112
0034608	8 x 0.50	8.7	70.0	135
0034610	10 x 0.50	9.3	88.0	160
0034612	12 x 0.50	9.6	99.0	177
0034618	18 x 0.50	11.8	134.0	239
0034620	20 x 0.50	12.1	149.0	276
0034625	25 x 0.50	13.7	211.0	352
0034630	30 x 0.50	14.5	230.0	397
0034702	2 x 0.75	6.0	38.0	64
0034703	3 x 0.75	6.3	49.0	76
0034704	4 x 0.75	7.0	58.0	92
0034705	5 x 0.75	7.6	67.0	109
0034707	7 x 0.75	8.2	100.0	156
0034710	10 x 0.75	10.5	130.0	187
0034712	12 x 0.75	10.8	154.0	218
0034718	18 x 0.75	13.0	195.0	327
0034725	25 x 0.75	15.3	280.0	454
0034730	30 x 0.75	15.8	312.0	486
0034802	2 x 1.00	6.3	43.0	72
0034803	3 x 1.00	6.8	56.0	90
0034804	4 x 1.00	7.3	68.0	109
0034805	5 x 1.00	8.0	79.0	126
0034807	7 x 1.00	8.6	118.0	171
0034810	10 x 1.00	11.1	140.0	228
0034812	12 x 1.00	11.4	168.0	259
0034818	18 x 1.00	13.4	252.0	389
0034825	25 x 1.00	16.2	335.0	517
0034902	2 x 1.50	7.1	58.0	90
0034903	3 x 1.50	7.5	74.0	115
0034904	4 x 1.50	8.1	108.0	153
0034905	5 x 1.50	8.8	129.0	176
0034907	7 x 1.50	9.5	164.0	220
0034912	12 x 1.50	12.7	254.0	376
0034918	18 x 1.50	15.3	350.0	519
0034925	25 x 1.50	17.9	550.0	901

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs are not to scale and do not represent detailed images of the respective products.

Similar products

- UNITRONIC® LiYCY (TP) refer to page 251
- UNITRONIC® PUR CP refer to page 258
- UNITRONIC® LiYCY A refer to page 267

Accessories

- SKINTOP® MS-SC refer to page 733
- Multipurpose shears A and B refer to page 907
- UNIVERSAL STRIP stripping and cutting tool refer to page 910