



UNITRONIC® SPIRAL

Spiral cable with outer PUR sheath and overall shielding for exact impulse transmission



Info

- Secure against electrical interferences
- PUR outer sheath

Benefits

- Overall screening prevents high frequency interference and guarantees accurate signal transmission
- Extended lengths of up to 4 times the unextended spiral length

Application range

- In measurement and control engineering
- Wherever screened cables with smallest dimensions are required

Product features

- Abrasion and cut-resistant
- Very high flexibility

Product make-up

- Strands of bare copper wires
- Core insulation: Based on PVC
- Screening: wrapped with braided copper wires
- Outer sheath: PUR compound
- Versions without the mandatory LAPP designation, but with other solid lengths, end lengths and end forms available on request

Technical data

- Core identification code**
DIN 47100
- Peak operating voltage**
250 V (not for power transmission)
- Specific insulation resistance**
> 10 GOhm x cm
- Conductor stranding**
Extra-fine wire according to VDE 0295, class 6/IEC 60228 class 6
- Test voltage**
1200 V
- Temperature range**
Flexing: -5°C to +50°C

Article number	Number of cores and mm ² per conductor	Spiral length, extended (mm)	Spiral length, unextended (mm)	Cable diameter (mm)	Spiral outer diameter (mm)	Copper index kg/1.000 pieces	Pieces / PU
73220200	2 x 0.14	400	100	4.1	15.0	16.5	5
73220201	2 x 0.14	800	200	4.1	15.0	23.8	5
73220202	2 x 0.14	1,200	300	4.1	15.0	29.7	5
73220203	2 x 0.14	1,600	400	4.1	15.0	36.9	5
73220204	2 x 0.14	2,000	500	4.1	15.0	48.0	5
73220205	3 x 0.14	400	100	4.3	18.0	21.0	5
73220206	3 x 0.14	800	200	4.3	18.0	30.8	5
73220207	3 x 0.14	1,200	300	4.3	18.0	43.5	5
73220208	3 x 0.14	1,600	400	4.3	18.0	54.8	5
73220209	3 x 0.14	2,000	500	4.3	18.0	63.8	5
73220210	4 x 0.14	400	100	4.5	19.0	23.4	5
73220211	4 x 0.14	800	200	4.5	19.0	33.6	5
73220212	4 x 0.14	1,200	300	4.5	19.0	45.8	5
73220213	4 x 0.14	1,600	400	4.5	19.0	58.6	5
73220214	4 x 0.14	2,000	500	4.5	19.0	67.2	5
73220215	5 x 0.14	400	100	4.8	20.0	24.4	5
73220216	5 x 0.14	800	200	4.8	20.0	38.1	5
73220217	5 x 0.14	1,200	300	4.8	20.0	50.4	5
73220218	5 x 0.14	1,600	400	4.8	20.0	60.4	5
73220219	5 x 0.14	2,000	500	4.8	20.0	72.0	5
73220220	6 x 0.14	400	100	5.5	21.0	31.1	5
73220221	6 x 0.14	800	200	5.5	21.0	44.8	5
73220222	6 x 0.14	1,200	300	5.5	21.0	56.3	5
73220223	6 x 0.14	1,600	400	5.5	21.0	77.9	5
73220224	6 x 0.14	2,000	500	5.5	21.0	73.9	5
73220230	12 x 0.14	400	100	7.2	27.0	56.4	1
73220231	12 x 0.14	800	200	7.2	27.0	95.2	1
73220232	12 x 0.14	1,200	300	7.2	27.0	118.1	1
73220233	12 x 0.14	1,600	400	7.2	27.0	161.0	1
73220234	12 x 0.14	2,000	500	7.2	27.0	179.2	1
73220235	18 x 0.14	400	100	8.0	29.0	75.1	1
73220236	18 x 0.14	800	200	8.0	29.0	110.5	1
73220237	18 x 0.14	1,200	300	8.0	29.0	150.2	1
73220238	18 x 0.14	1,600	400	8.0	29.0	198.9	1
73220239	18 x 0.14	2,000	500	8.0	29.0	221.0	1

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
 Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
 Photographs are not to scale and do not represent detailed images of the respective products.
 Versions without the mandatory LAPP designation, but with other solid lengths, end lengths and end forms available on request

Accessories

- SKINTOP® CLICK System refer to page 657